

**SECTION 09653 - RESILIENT WALL BASE AND ACCESSORIES****PART 1 - GENERAL****1.1 SECTION REQUIREMENTS**

- A. Submittals: Product Data and Samples.
- B. Extra Materials: Deliver to Owner at least 50 linear feet, of each type and color of resilient wall base installed.

**PART 2 - PRODUCTS****2.1 WALL BASE**

- A. Basis of Design Products:
  - 1. Tarkett; Nafco
- B. Color and Pattern: To be determined
- C. ASTM F 1861, Type TV (vinyl).
- D. Group (Manufacturing Method): II (layered).
- E. Style: Cove (with top-set toe).
- F. Minimum Thickness: 0.125 inch (3.2 mm).
- G. Height: 4 inches (101.6 mm).
- H. Lengths: coils in manufacturer's standard lengths.
- I. Outside Corners: premolded.
- J. Inside Corners: premolded.

**2.2 RESILIENT ACCESSORY**

- A. Products:
  - 1. To be determined.
- B. Color: To be determined.
- C. Description: Carpet edge for glue-down applications, nosing for carpet, nosing for resilient floor covering, reducer strip for resilient floor covering, and joiner for tile and carpet.

- D. Material: Vinyl.
- E. Profile and Dimensions: To be determined.

2.3 INSTALLATION ACCESSORIES

- A. Trowelable Leveling and Patching Compounds: Latex-modified, portland cement- or blended hydraulic cement-based formulation provided or approved by flooring manufacturer for applications indicated.
- B. Adhesives: Water-resistant type recommended by manufacturer to suit products and substrate conditions.

PART 3 - EXECUTION

3.1 INSTALLATION

- A. Prepare concrete substrates according to ASTM F 710. Verify that substrates are dry and free of curing compounds, sealers, and hardeners.
- B. Adhesively install resilient wall base and accessories.
- C. Install wall base in maximum lengths possible. Apply to walls, columns, pilasters, casework, and other permanent fixtures in rooms or areas where base is required.
- D. Install reducer strips at edges of floor coverings that would otherwise be exposed.

END OF SECTION 09653